

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

**AS31971**

Submitted for recognition as an American National Standard

FEDERAL SUPPLY CLASS  
5220

## NOTICE

This document has been taken directly from U.S. Military Standard, MS3197G, and contains only minor editorial and format changes required to bring it into conformance with the publishing requirements of SAE technical standards.

The original Military Standard was adopted as an SAE standard under the provisions of the SAE Technical Standards Board (TSB) Rules and Regulations (TSB 001) pertaining to accelerated adoption of government specifications and standards. TSB rules provide for (a) the publication of portions of unrevised government specifications and standards without consensus voting at the SAE Committee level, (b) the use of the existing government specification or standard format, and (c) the exclusion of any qualified product list (QPL) sections.

ISSUED 1997-10


PREPARED BY SUBCOMMITTEE AE-8C1

**SAE** The Engineering Society  
For Advancing Mobility  
Land Sea Air and Space®  
**INTERNATIONAL**  
400 Commonwealth Drive, Warrendale, PA 15096-0001

## AEROSPACE STANDARD

GAGE PIN FOR SOCKET  
CONTACT ENGAGEMENT TEST

**AS31971**  
SHEET 1 OF 2



| Dash No. | Contact size | A                       |                         | B        | Gage pin material              |        |    |        |    |
|----------|--------------|-------------------------|-------------------------|----------|--------------------------------|--------|----|--------|----|
|          |              | Min<br>+.0001<br>-.0000 | Max<br>+.0000<br>-.0001 | Max flat |                                |        |    |        |    |
| -24X1    | 24           | .0245                   |                         | .007     | Tool Steel or Tungsten Carbide | INCHES | MM | INCHES | MM |
| -24Y1    |              |                         | .0255                   |          |                                |        |    |        |    |
| -23X1    | 23           | .0260                   |                         |          |                                |        |    |        |    |
| -23Y1    |              |                         | .0275                   |          |                                |        |    |        |    |
| -22X1    | 22           | .0295                   |                         |          |                                |        |    |        |    |
| -22Y1    |              |                         | .0305                   |          |                                |        |    |        |    |
| -20X1    | 20           | .0390                   |                         | .015     | Tungsten Carbide               | INCHES | MM | INCHES | MM |
| -20Y1    |              |                         | .0410                   |          |                                |        |    |        |    |
| -16X1    | 16           | .0615                   |                         |          |                                |        |    |        |    |
| -16Y1    |              |                         | .0635                   |          |                                |        |    |        |    |
| -12X1    | 12           | .0930                   |                         |          |                                |        |    |        |    |
| -12Y1    |              |                         | .0950                   |          |                                |        |    |        |    |
| -10X1    | 10           | .1240                   |                         |          |                                |        |    |        |    |
| -10Y1    |              |                         | .1260                   |          |                                |        |    |        |    |
| -8X1     | 8            | .1410                   |                         |          |                                |        |    |        |    |
| -8Y1     |              |                         | .1430                   |          |                                |        |    |        |    |
| -6X1     | 6            | .1770                   |                         |          |                                |        |    |        |    |
| -6Y1     |              |                         | .1790                   |          |                                |        |    |        |    |
| -4X1     | 4            | .2240                   |                         | .030     | Tungsten Carbide               | INCHES | MM | INCHES | MM |
| -4Y1     |              |                         | .2260                   |          |                                |        |    |        |    |
| -2X1     | 2            | .2820                   |                         |          |                                |        |    |        |    |
| -2Y1     |              |                         | .2840                   |          |                                |        |    |        |    |
| -0X1     | 0            | .3560                   |                         |          |                                |        |    |        |    |
| -0Y1     |              |                         | .3580                   |          |                                |        |    |        |    |
| -4/0X1   | 4/0          | .4990                   |                         | .060     | Tungsten Carbide               | INCHES | MM | INCHES | MM |
| -4/0Y1   |              |                         | .5010                   |          |                                |        |    |        |    |

## NOTES:

- DIMENSIONS ARE IN INCHES.
- MATERIAL: GAGE PIN, AS SHOWN IN TABLE; HANDLE, OPTIONAL.
- FINISH: 6 TO 10 MICROINCHES ROOT MEAN SQUARE DETERMINED IN ACCORDANCE WITH ANSI B46.1.
- PLATING: NONE.
- THESE GAGES ARE INTENDED FOR USE WITH ELECTRIC CONNECTOR SOCKET CONTACTS IN ACCORDANCE WITH MIL-C-39029 AND OTHER SPECIFICATIONS REFERENCING THIS DOCUMENT.
- FOR DESIGN PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.